

Model Number H01QDC9JA2AN
Serial Number 752TVVL454

CPS Channels Summary

Channels

Alvah-Temp Channel Pool

- 1 CH 1
- 2 CH 2
- 3 CH 3
- 4 CH 4
- 5 CH 5
- 6 CH 6
- 7 CH 7
- 8 CH 8
- 9 CH 9
- 10 CH 10
- 11 CH 11
- 12 CH 12
- 13 CH 13
- 14 CH 14
- 15 CH 15
- 16 CH 16

Alvah-Temp

	CH 1	CH 2	CH 3	CH 4	CH 5
Position	1	2	3	4	5
Channel Type	Analog	Analog	Analog	Analog	Analog
Voice Announcement File	N/A	N/A	N/A	N/A	N/A
Channel Bandwidth (kHz)	12.5	12.5	12.5	12.5	12.5
Scan/Roam List	None	None	None	None	None
Auto Scan	N/A	N/A	N/A	N/A	N/A
Squelch	Normal	Normal	Normal	Normal	Normal
Voice Emphasis	De & Pre	De & Pre	De & Pre	De & Pre	De & Pre
ARTS	Disabled	Disabled	Disabled	Disabled	Disabled
Lone Worker	N/A	N/A	N/A	N/A	N/A
Allow Talkaround	N/A	N/A	N/A	N/A	N/A
Audio Enhancement	None	None	None	None	None
Scrambling Enable	No	No	No	No	No
RX Only	No	No	No	No	No
RX					
Frequency (MHz)	451.8	451.8125	456.8	456.8125	451.8
Squelch Type	DPL	DPL	DPL	DPL	DPL
DPL Code (Octal)	546	546	546	546	131
DPL Invert	No	No	No	No	No
TPL Frequency (Hz)	N/A	N/A	N/A	N/A	N/A
TPL Code	N/A	N/A	N/A	N/A	N/A

Signaling System	None	None	None	None	None
Ref Frequency (MHz)	Default	Default	Default	Default	Default
Signaling Squelch	N/A	N/A	N/A	N/A	N/A
Unmute Rule	Std Unmute, Mute	Std Unmute, Mute	Std Unmute, Mute	Std Unmute, Mute	Std Unmute, Mute
Emergency Alarm Indication	No	No	No	No	No
Emergency Alarm Ack	N/A	N/A	N/A	N/A	N/A
PL for Data	N/A	N/A	N/A	N/A	N/A

TX

Frequency (MHz)	451.8	451.8125	456.8	456.8125	451.8
Squelch Type	DPL	DPL	DPL	DPL	DPL
DPL Code (Octal)	546	546	546	546	131
DPL Invert	No	No	No	No	No
TPL Frequency (Hz)	N/A	N/A	N/A	N/A	N/A
TPL Code	N/A	N/A	N/A	N/A	N/A
Signaling System	None	None	None	None	None
Ref Frequency (MHz)	Default	Default	Default	Default	Default
DPL Turn-Off Code	Yes	Yes	Yes	Yes	Yes
VOX	N/A	N/A	N/A	N/A	N/A
TPL Reverse Burst	N/A	N/A	N/A	N/A	N/A
Power Level	High	High	High	High	High
TOT (sec)	60	60	60	60	60
TOT Rekey Delay (sec)	0	0	0	0	0
Admit Criteria	Always	Always	Always	Always	Always
RSSI Threshold (dBm)	N/A	N/A	N/A	N/A	N/A
Repeater Access ID	N/A	N/A	N/A	N/A	N/A
ARTS Interval (sec)	N/A	N/A	N/A	N/A	N/A

CH 6**CH 7****CH 8****CH 9****CH 10**

Position	6	7	8	9	10
Channel Type	Analog	Analog	Analog	Digital	Digital
Voice Announcement File	N/A	N/A	N/A	N/A	N/A
Channel Bandwidth (kHz)	12.5	12.5	12.5	N/A	N/A
Dual Capacity Direct Mode	N/A	N/A	N/A	Yes	Yes
Timing Leader Preference	N/A	N/A	N/A	Eligible	Eligible
Scan/Roam List	None	None	None	None	None
Auto Scan	N/A	N/A	N/A	N/A	N/A
Squelch	Normal	Normal	Normal	N/A	N/A
Voice Emphasis	De & Pre	De & Pre	De & Pre	N/A	N/A
ARTS	Disabled	Disabled	Disabled	N/A	N/A
Color Code	N/A	N/A	N/A	3	3
Extended Range Direct Mode	N/A	N/A	N/A	Disabled	Disabled
Inbound Color Code	N/A	N/A	N/A	N/A	N/A
Outbound Color Code	N/A	N/A	N/A	N/A	N/A
Repeater/Time Slot	N/A	N/A	N/A	1	2
ARS	N/A	N/A	N/A	Disabled	Disabled
Privacy	N/A	N/A	N/A	No	No
RAS Alias	N/A	N/A	N/A	None	None
Lone Worker	N/A	N/A	N/A	N/A	N/A
Allow Talkaround	N/A	N/A	N/A	N/A	N/A
Over-the-Air Battery Management	N/A	N/A	N/A	No	No
Compressed UDP Data Header	N/A	N/A	N/A	None	None
Audio Enhancement	None	None	None	N/A	N/A

Scrambling Enable	No	No	No	N/A	N/A
RX Only	No	No	No	No	No
RX					
Frequency (MHz)	451.8125	456.8	456.8125	457.5375	457.5375
Squelch Type	DPL	DPL	DPL	N/A	N/A
DPL Code (Octal)	131	131	131	N/A	N/A
DPL Invert	No	No	No	N/A	N/A
TPL Frequency (Hz)	N/A	N/A	N/A	N/A	N/A
TPL Code	N/A	N/A	N/A	N/A	N/A
Signaling System	None	None	None	N/A	N/A
Ref Frequency (MHz)	Default	Default	Default	Default	Default
Signaling Squelch	N/A	N/A	N/A	N/A	N/A
Unmute Rule	Std Unmute, Mute	Std Unmute, Mute	Std Unmute, Mute	N/A	N/A
Group List	N/A	N/A	N/A	DigitalRXGroupList/List1	None
Emergency Alarm Indication	No	No	No	N/A	N/A
Emergency Alarm Ack	N/A	N/A	N/A	N/A	N/A
PL for Data	N/A	N/A	N/A	N/A	N/A
TX					
Frequency (MHz)	451.8125	456.8	456.8125	N/A	N/A
Squelch Type	DPL	DPL	DPL	N/A	N/A
DPL Code (Octal)	131	131	131	N/A	N/A
DPL Invert	No	No	No	N/A	N/A
TPL Frequency (Hz)	N/A	N/A	N/A	N/A	N/A
TPL Code	N/A	N/A	N/A	N/A	N/A
Signaling System	None	None	None	N/A	N/A
Ref Frequency (MHz)	Default	Default	Default	N/A	N/A
DPL Turn-Off Code	Yes	Yes	Yes	N/A	N/A
Contact Name	N/A	N/A	N/A	Grp 1	Grp 2
VOX	N/A	N/A	N/A	No	No
TPL Reverse Burst	N/A	N/A	N/A	N/A	N/A
Power Level	High	High	High	High	High
TOT (sec)	60	60	60	60	60
TOT Rekey Delay (sec)	0	0	0	0	0
Allow Interruption	N/A	N/A	N/A	No	No
TX Interruptible Frequencies	N/A	N/A	N/A	N/A	N/A
Admit Criteria	Always	Always	Always	Always	Always
In Call Criteria	N/A	N/A	N/A	Always	Always
RSSI Threshold (dBm)	N/A	N/A	N/A	N/A	N/A
Repeater Access ID	N/A	N/A	N/A	N/A	N/A
ARTS Interval (sec)	N/A	N/A	N/A	N/A	N/A
Private Call Confirmed	N/A	N/A	N/A	No	No
Data Call Confirmed	N/A	N/A	N/A	Yes	Yes
Enhanced Channel Access	N/A	N/A	N/A	N/A	N/A
	CH 11	CH 12	CH 13	CH 14	CH 15
Position	11	12	13	14	15
Channel Type	Digital	Digital	Digital	Digital	Digital
Voice Announcement File	N/A	N/A	N/A	N/A	N/A
Dual Capacity Direct Mode	Yes	No	No	No	No
Timing Leader Preference	Eligible	N/A	N/A	N/A	N/A
Scan/Roam List	None	None	None	None	None
Auto Scan	N/A	N/A	N/A	N/A	N/A

Color Code	3	3	3	3	3
Extended Range Direct Mode	Disabled	Disabled	Disabled	Disabled	Disabled
Inbound Color Code	N/A	N/A	N/A	N/A	N/A
Outbound Color Code	N/A	N/A	N/A	N/A	N/A
Repeater/Time Slot	1	2	1	2	1
ARS	Disabled	Disabled	Disabled	Disabled	Disabled
Privacy	No	No	No	No	No
RAS Alias	None	None	None	None	None
Allow Talkaround	N/A	N/A	N/A	N/A	N/A
Over-the-Air Battery Management	No	No	No	No	No
Compressed UDP Data Header	None	None	None	None	None
RX Only	No	No	No	No	No

RX

Frequency (MHz)	457.55	457.55	457.5625	457.5625	457.575
Ref Frequency (MHz)	Default	Default	Default	Default	Default
Group List	None	None	None	None	None

TX

Frequency (MHz)	N/A	457.55	457.5625	457.5625	457.575
Ref Frequency (MHz)	N/A	Default	Default	Default	Default
Contact Name	Grp 3	Grp 4	Grp 5	Grp 6	Grp 7
VOX	No	No	No	No	No
Power Level	High	High	High	High	High
TOT (sec)	60	60	60	60	60
TOT Rekey Delay (sec)	0	0	0	0	0
Allow Interruption	No	No	No	No	No
TX Interruptible Frequencies	N/A	N/A	N/A	N/A	N/A
Admit Criteria	Always	Always	Always	Always	Always
In Call Criteria	Follow Admit Criteria	Always	Always	Always	Always
RSSI Threshold (dBm)	N/A	N/A	N/A	N/A	N/A
Private Call Confirmed	No	No	No	No	No
Data Call Confirmed	Yes	Yes	Yes	Yes	Yes
Enhanced Channel Access	N/A	N/A	N/A	N/A	N/A

CH 16

Position	16
Channel Type	Digital
Voice Announcement File	N/A
Dual Capacity Direct Mode	No
Timing Leader Preference	N/A
Scan/Roam List	None
Auto Scan	N/A
Color Code	3
Extended Range Direct Mode	Disabled
Inbound Color Code	N/A
Outbound Color Code	N/A
Repeater/Time Slot	2
ARS	Disabled
Privacy	No
RAS Alias	None
Allow Talkaround	N/A
Over-the-Air Battery	

Management	No
Compressed UDP Data Header	None
RX Only	No
RX	
Frequency (MHz)	457.575
Ref Frequency (MHz)	Default
Group List	None
TX	
Frequency (MHz)	457.575
Ref Frequency (MHz)	Default
Contact Name	Grp 8
VOX	No
Power Level	High
TOT (sec)	60
TOT Rekey Delay (sec)	0
Allow Interruption	No
TX Interruptible Frequencies	N/A
Admit Criteria	Always
In Call Criteria	Always
RSSI Threshold (dBm)	N/A
Private Call Confirmed	No
Data Call Confirmed	Yes
Enhanced Channel Access	N/A

Channel Pool